

EnduraMax™ Direct-Drive Fan Specifications

Composite Shroud & Shutter Doors / HDPE Cone

STANDARD MOUNT		U.S. MEASURE				METRIC				Air Flow Ratio	BESS Lab Test No.	Power
Fan Kit Part No.	Speed Setting RPM / Hz	Static Pressure .10"		Static Pressure .15"		Static Pressure 25 Pa		Static Pressure 37 Pa				
		CFM	CFM/Watt	CFM	CFM/Watt	CMH	CMH/Watt	CMH	CMH/Watt			
57611-11* Tested at 60 Hz	630 / 84.0	35700	17.3	34200	15.7	60700	29.4	58200	26.7	0.88	24694	230V 1 Ph
	575 / 76.7	32700	20.0	30600	17.6	55500	33.9	52000	30.0	0.84		
	500 / 66.7	27500	23.9	25100	20.3	46800	40.7	42700	34.5	0.76		
	450 / 60.0	23900	27.0	20900	21.6	40700	45.9	35500	36.7	0.63		
	400 / 53.3	18800	26.9	13700	19.0	32000	45.7	23200	32.2	0.42		
	350 / 46.7	13700	27.0	8400	15.1	23400	45.9	14200	25.7	NA		

*Note: fan sub-assembly 57611-1P and VFD 58142-1



Let's grow together®

www.choretime.com

Find your authorized independent distributor at choretime.com/distributor

Chore-Time
Milford, Indiana USA
info@choretime.com

Chore-Time Europe B.V.
Panningen, Netherlands
info@choretime.nl

Chore-Time Europe Sp. z o.o.
Strykowo, Poland
info@choretime.pl

Chore-Time Ede B.V.
Ede, Netherlands
info@choretime.nl